



——为您甄选优质产品

——QUALITY PRODUCTS AND SERVICES

山东晟拖重工有限公司

SHANDONG SHENGTUO HEAVY INDUSTRY CO., LTD.

产品手册

>>>

PRODUCT MANUAL
TRACTOR SERIES

拖拉机 Wheel Tractor



ST2204 (200&220hp) Series Tractor



CHARACTERISTICS:

- Italy CARRARO double-cylinder front drive axle has a high reliability.
- German Luk clutch has a high reliability, and the optional hydraulic power steering system can improve the manipulation, And equip with the radial tyres.
- Optional German Rexroth electrically controlled lifter can achieve force adjustment, position adjustment, force-position control, and floating control, three point suspension use the cat. III.
- 16+16 synchronizer shift with a wide speed range can adapt to various operations. The use of shuttle shift structure makes the manipulation more convenient.
- 350-liter lower large fuel tank, a long operation time.

技术参数 / TECHNICAL PARAMETERS:

发动机功率 (千瓦) / Rated Engine Power (Kw)	147/162	轴距 (毫米) / Wheel Base (mm)	2830
驱动形式 / Driven Type	4x4 轮式 4WD	档位 / Shifts	16+16
长 (毫米) / Length (mm)	5500	最大牵引力 (四轮驱动) (千牛) / Max Tractor (4WD) (KN)	>39.4
宽 (毫米) / Width (mm)	2780 (双排轮宽 Double Rear Tyre 3540)	前进速度范围 (千米/小时) / Forward Speed Range (Km/h)	3.14-30.53
高 (毫米) / Height (mm)	3200	倒退速度范围 (千米/小时) / Reverse Speed (Km/h)	2.74-25.66
前轮轮距 (毫米) / Tread of Front Wheel (mm)	1720/1820/1980/2100	动力输出轴 (转/分) / PTO (Rev./min)	540/1000
后轮轮距 (毫米) / Tread of Rear Wheel (mm)	1700-2500		

ST2004 (200&210 hp) Series Tractor



CHARACTERISTICS:

- Famous brand front drive axle has a high reliability.
- Matched with desert air filter(specially manufactured for Weichai), which has higher Reliability, more advanced and excellent performance in harsh environment and weight bearing operation.
- Tractor clutch has a high reliability, and the optional hydraulic power steering system can improve the manipulation.
- Optional electrically controlled lifter can achieve force adjustment, position adjustment, force-position control, and floating control.
- 16+8 shift with a wide speed range can adapt to various operations. The use of shuttle shift structure makes the manipulation more convenient.
- 350-liter lower large fuel tank, a long operation time.

技术参数 / TECHNICAL PARAMETERS:

发动机功率 (千瓦) / Rated Engine Power(Kw)	147/155	轴距 (毫米) / Wheel Base(mm)	2660
驱动形式 / Driven Type	4×4 轮式 4WD	档位 / Shifts	16+8
长 (毫米) / Length (mm)	5250	最大牵引力 (四轮驱动) (千牛) / Max Traction (4WD)(KN)	≥35.8
宽 (毫米) / Width (mm)	2330	前进速度范围 (千米/小时) / Forward Speed Range(Km/h)	1.52-30.77
高 (毫米) / Height (mm)	3100	倒退速度范围 (千米/小时) / Reverse Speed (Km/h)	2.37-28.41
前轮轮距 (毫米) / Tread of Front Wheel(mm)	1680/1750/1790/1830/1850	动力输出轴 (转/分) / PTO(Rot./min)	760/850 (选装 Optional 540/1000)
后轮轮距 (毫米) / Tread of Rear Wheel(mm)	1600-1900	PTO 花键数 / PTO spline number	6
轮胎规格 / Tire specifications	14.9-26/18.4-38	操作重量 / Operating weight	7075

选装: 风冷驾驶室 / 暖风驾驶室 / 空调驾驶室 / 摆式牵引 / 后视镜系统 / 三叉悬挂 / 加宽轮胎 / 电控提升 / 双轮偏心胎
Optional: Fan cab / Heating cab / Air-conditioned cab / Swing draw bar / Rear view system / CAT III / Widened tire / Electronic control lifter / Twin eccentric wheel

ST1804 (180hp) Series Tractor



技术参数 / TECHNICAL PARAMETERS:

额定功率 (千瓦) / Rated Engine Power(Kw)	132.5	轴距 (毫米) / Wheel Base(mm)	2650
驱动形式 / Drive Type	4×4 轮式 4WD	档位 / Shifts	16+8
长 (毫米) / Length (mm)	5050	最大牵引力 (四轮驱动) (千牛) / Max Traction (4WD)(KN)	>28
宽 (毫米) / Width (mm)	2250	前进速度范围 (千米/小时) / Forward Speed Range(Km/h)	1.6-33.7
高 (毫米) / Height (mm)	3020	倒退速度范围 (千米/小时) / Reverse Speed (Km/h)	2.4-34.7
前轮轮胎 (毫米) / Tread of Front Wheel(mm)	1680/1750/1790/1830	动力输出轴 (转/分) / PTO(Rot/min)	740/850
后轮轮胎 (毫米) / Tread of Rear Wheel(mm)	1600-1900	PTO 花键数 / PTO spline number	6
轮胎规格 / Tire specifications	14.9-26/18.4-38	操作重量 / Operating weight	6475

选装: 风扇驾驶室 / 暖风驾驶室 / 空调驾驶室 / 摆式牵引 / 后视系统
Optional: Fan cab / Heating cab / Air-conditioned cab / Swing draw bar / Rear view system

CHARACTERISTICS:

- Famous brand front drive axle has a high reliability.
- Matched with desert air filter(specially manufactured for Weichai), which has higher Reliability, more advanced and excellent performance in harsh environment and weight bearing operation.
- Tractor clutch has a high reliability, and the optional hydraulic power steering system can improve the manipulation.
- Optional electrically controlled lifter can achieve force adjustment, position adjustment, force-position control, and floating control.
- 16+8 shift with a wide speed range can adapt to various operations. The use of shuttle shift structure makes the manipulation more convenient.
- 350-liter lower large fuel tank, a long operation time.

ST1604 (140&150&160hp) Series Tractor



技术参数 / TECHNICAL PARAMETERS:

发动机功率 (千瓦) / Rated Engine Power(Kw)	102.9/110.3/117.6	轴距 (毫米) / Wheel Base(mm)	2680
驱动形式 / Drive Type	4×4 轮式 4WD	档位 / Shifts	16+8
长 (毫米) / Length (mm)	5180	最大牵引力 (四轮驱动) (千牛) / Max Traction (4WD)(KN)	≥28
宽 (毫米) / Width(mm)	2300	前进速度范围 (千米/小时) / Forward Speed Range(Km/h)	1.6-33.7
高 (毫米) / Height (mm)	3000	倒退速度范围 (千米/小时) / Reverse Speed (Km/h)	2.4-34.7
前轮轮距 (毫米) / Tread of Front Wheel(mm)	1750/1790/1830/1850	动力输出轴 (转/分) / PTO(Rcv./min)	760/850
后轮轮距 (毫米) / Tread of Rear Wheel(mm)	1600-1900	PTO 花键数 / PTO spline number	6
轮胎规格 / Tire specifications	14.9-26/18.4-38	操作重量 / Operating weight	6505

选装：风箱驾驶室 / 暖风驾驶室 / 空调驾驶室 / 摆式牵引 / 后视系统
Optional: Fan cab / Heating cab / Air-conditioned cab / Swing draw bar / Rear view system

CHARACTERISTICS:

- Famous brand front drive axle has a high reliability.
- Matched with desert air filter(specially manufactured for Weichai), which has higher Reliability, more advanced and excellent performance in harsh environment and weight bearing operation.
- Tractor clutch has a high reliability, and the optional hydraulic power steering system can improve the manipulation.
- Optional electrically controlled lifter can achieve force adjustment, position adjustment, force-position control, and floating control.
- 16+8 shift with a wide speed range can adapt to various operations. The use of shuttle shift structure makes the manipulation more convenient.
- 350-liter lower large fuel tank, a long operation time.

ST1004 (90&100&120hp) Series Tractor



技术参数 / TECHNICAL PARAMETERS:

发动机功率 (千瓦) / Rated Engine Power(Kw)	66.2/73.5/88.2	轴距 (毫米) / Wheel Base(mm)	2380
驱动形式 / Driven Type	4×4 轮式 4WD	档位 / Shifts	16+8
长 (毫米) / Length (mm)	4350	最大牵引力 (四轮驱动) (千牛) / Max.Traction (4WD)(kN)	≥28
宽 (毫米) / Width(mm)	2130	前进速度范围 (千米 / 小时) / Forward Speed Range(Km/h)	1.6-33.7
高 (毫米) / Height (mm)	2840	倒退速度范围 (千米 / 小时) / Reverse Speed (Km/h)	2.4-34.7
前轮轮距 (毫米) / Tread of Front Wheel(mm)	1625	动力输出轴 (转 / 分) / PTO(Rex./min)	760/850
后轮轮距 (毫米) / Tread of Rear Wheel(mm)	1608-1996	PTO 花键数 / PTO spline number	6
轮胎规格 / Tire specifications	13.6-24/16.9-34	操作重量 / Operating weight	4500

选装: 风扇驾驶室 / 暖风驾驶室 / 空调驾驶室 / 摆式牵引 / 后视镜系统
Optional: Fan cab / Heating cab / Air-conditioned cab / Swing draw bar / Rear view system

CHARACTERISTICS:

- Famous brand front drive axle has a high reliability.
- Matched with desert air filter(specially manufactured for Weichai), which has higher Reliability, more advanced and excellent performance in harsh environment and weight bearing operation.
- Tractor clutch has a high reliability, and the optional hydraulic power steering system can improve the manipulation.
- Optional electrically controlled lifter can achieve force adjustment, position adjustment, force-position control, and floating control.
- 16+8 shift with a wide speed range can adapt to various operations. The use of shuttle shift structure makes the manipulation more convenient.
- 350-liter lower large fuel tank, a long operation time.

ST1004 (90&100hp) Series Tractor



技术参数 / TECHNICAL PARAMETERS:

发动机功率 (千瓦) / Rated Engine Power(Kw)	66.2/73.6	轴距 (毫米) / Wheel Base(mm)	2050
驱动形式 / Driven Type	4×4 轮式 4WD	档位 / Shifts	12+12
长 (毫米) / Length (mm)	4050	最大牵引力 (四轮驱动) (千牛) / Max Traction (4WD)(KN)	≥18
宽 (毫米) / Width (mm)	1830	前进速度范围 (千米/小时) / Forward Speed Range(Km/h)	2.46-32.73
高 (毫米) / Height (mm)	2660	倒退速度范围 (千米/小时) / Reverse Speed (Km/h)	2.15-28.69
前轮轮距 (毫米) / Tread of Front Wheel(mm)	1300(1400/1450)	动力输出轴 (转/分) / PTO(Rev./min)	540/760
后轮轮距 (毫米) / Tread of Rear Wheel(mm)	1380(1300-1500)	PTO 花键数 / PTO spline number	6
轮胎规格 / Tire specifications	9.5-24/14.9-30	操作重量 / Operating weight	3119-3189

选装: 风窗驾驶室 / 暖风驾驶室 / 空调驾驶室 / 摆式牵引 / 防翻架 / 遮阳篷
Optional: Fan cab / Heating cab / Air-conditioned cab / Swing draw bar / ROPS / Canopy

CHARACTERISTICS:

- The famous brand front drive axle is highly reliable.
- The distribution of gears is reasonable, high agronomic adaptability, a variety of farmland operations and transport operations with higher productivity, greater fuel economy and more advanced technology. Reasonable speed matching, high working efficiency and excellent adaptability.
- The power output speed can be selected from various speeds, such as 540/760 rpm, and it can be equipped with a variety of agricultural machines and tools that have a wider adaptation range.

ST904 (90&100hp) Series Tractor



技术参数 / TECHNICAL PARAMETERS:

发动机功率 (千瓦) / Rated Engine Power(Kw)	66.2/73.6	轴距 (毫米) / Wheel Base(mm)	2050
驱动形式 / Driven Type	4×4 轮式 4WD	档位 / Shifts	12+12
长 (毫米) / Length (mm)	4050	最大牵引力 (四轮驱动) (千牛) / Max Traction (4WD)(KN)	≥18
宽 (毫米) / Width(mm)	1630	前进速度范围 (千米/小时) / Forward Speed Range(Km/h)	2.46-32.73
高 (毫米) / Height (mm)	2660	倒退速度范围 (千米/小时) / Reverse Speed (Km/h)	2.15-28.69
前轮轮距 (毫米) / Tread of Front Wheel(mm)	1300/1400/1450	动力输出轴 (转/分) / PTO(Rov./min)	540/760
后轮轮距 (毫米) / Tread of Rear Wheel(mm)	1380(1300-1500)	PTO 花键数 / PTO spline number	6
轮胎规格 / Tire specifications	9.5-24/14.9-30	操作重量 / Operating weight	3119-3189

选装：风扇驾驶室 / 暖风驾驶室 / 空调驾驶室 / 摆式牵引 / 防翻架 / 遮阳蓬
Optional: Fan cab / Heating cab / Air-conditioned cab / Swing draw bar / ROPS / Canopy

CHARACTERISTICS:

- The famous brand front drive axle is highly reliable.
- The distribution of gears is reasonable, high agronomic adaptability, a variety of farmland operations and transport operations with higher productivity, greater fuel economy and more advanced technology. Reasonable speed matching, high working efficiency and excellent adaptability.
- The power output speed can be selected from various speeds, such as 540/760 rpm, and it can be equipped with a variety of agricultural machines and tools that have a wider adaptation range.

ST804 (70&80hp) Series Tractor



技术参数 / TECHNICAL PARAMETERS:

发动机功率 (千瓦) / Rated Engine Power(Kw)	51.5/58.8	轴距 (毫米) / Wheel Base(mm)	2010
驱动形式 / Driven Type	4×4 轮式 4WD	档位 / Shifts	8+2
长 (毫米) / Length (mm)	4050	最大牵引力 (四轮驱动) (千牛) / Max Traction (4WD)(KN)	>12
宽 (毫米) / Width (mm)	1795	前进速度范围 (千米/小时) / Forward Speed Range(Km/h)	2.26-34.21
高 (毫米) / Height (mm)	2630	倒退速度范围 (千米/小时) / Reverse Speed (Km/h)	2.10-31.86
前轮轮距 (毫米) / Tread of Front Wheel(mm)	1290/1390/1450	动力输出轴 (转/分) / PTO(Rev./min)	540/720
后轮轮距 (毫米) / Tread of Rear Wheel(mm)	1312/1376/1496	PTO 花键数 / PTO spline number	6
轮胎规格 / Tire specifications	8.3-24/14.9-30	操作重量 / Operating weight	3139

选装: 风扇驾驶室 / 暖风驾驶室 / 空调驾驶室 / 摆式牵引 / 防翻架 / 遮阳蓬
Optional: Fan cab / Heating cab / Air-conditioned cab / Swing draw bar / ROPS / Canopy

CHARACTERISTICS:

- Famous brand four-cylinder direct injection diesel engines with good fuel efficiency and high torque.
- Central console with simple design, high cost-effectiveness and easy maintenance.
- Completely new 8F + 4R gear shifting with reasonable speed and high efficiency.
- Agricultural tires, grass tires, engineering tires and many other tires for various working conditions.
- Suitable for greenhouse plants, orchards, vegetable gardens, etc.

ST804D (80&90hp) Series Tractor



技术参数 / TECHNICAL PARAMETERS:

发动机功率 (千瓦) / Rated Engine Power(Kw)	58.8/66.2	轴距 (毫米) / Wheel Base(mm)	1990
驱动形式 / Driven Type	4×4 轮式 4WD	档位 / Shifts	8+2
长 (毫米) / Length (mm)	3950	最大牵引力 (四轮驱动) (千牛) / Max.Traction (4WD)(KN)	17.7/16.7
宽 (毫米) / Width(mm)	1650	前进速度范围 (千米/小时) / Forward Speed Range(Km/h)	2.18-30.01
高 (毫米) / Height (mm)	2620/2560	倒退速度范围 (千米/小时) / Reverse Speed (Km/h)	2.07-6.51
前轮轮距 (毫米) / Tread of Front Wheel(mm)	1300	动力输出轴 (转/分) / PTO(Rav/min)	540/720
后轮轮距 (毫米) / Tread of Rear Wheel(mm)	1300		

选装: 风窗驾驶室 / 暖风驾驶室 / 空调驾驶室 / 防翻架 / 遮阳蓬
Optional: Fan cab / Heating cab / Air-conditioned cab / ROPS / Canopy

CHARACTERISTICS:

- Adopting a well-known American brand to strengthen and upgrade the chassis, the thickness of the shell is increased by 15%, and the strength is greatly improved.
- The gearbox and rear axle housing are made of ductile iron, which has twice the compressive strength of gray iron and higher reliability.
- It adopts a high-strength and airtight special front axle, which has good waterproofness and is purchased from the same channel as a well-known American brand, the overall structure design is more scientific and the ground clearance is large, which is more suitable for paddy field operations.
- Exquisite interiors and luxurious seats make driving more comfortable. The cab adopts an E-frame structure to better ensure the safety of the driver.
- Adopting the Moil large modulus taper transmission system, the gear modulus is adjusted from 2.75 to 3.0, and the strength is increased while improving the transmission stability and transmission efficiency.

ST604D (50&60hp) Series Tractor



技术参数 / TECHNICAL PARAMETERS:

发动机功率 (千瓦) / Rated Engine Power (Kw)	36.8/44.2/51.5/58.8	轴距 (毫米) / Wheel Base (mm)	1990
驱动形式 / Driven Type	4×4 轮式 4WD	档位 / Shifts	8+2
长 (毫米) / Length (mm)	3850	最大牵引力 (四轮驱动) (千牛) / Max Traction (4WD) (kN)	17.7/16.7
宽 (毫米) / Width (mm)	1450	前进速度范围 (千米/小时) / Forward Speed Range (Km/h)	2.18-30.01
高 (毫米) / Height (mm)	2420/2540	倒退速度范围 (千米/小时) / Reverse Speed (Km/h)	2.07-8.51
前轮轮距 (毫米) / Tread of Front Wheel (mm)	1300	动力输出轴 (转/分) / PTO (Rev/min)	540/720
后轮轮距 (毫米) / Tread of Rear Wheel (mm)	1300		

选装: 风扇驾驶室 / 暖风驾驶室 / 空调驾驶室 / 防翻架 / 遮阳蓬

Optional: Fan cab / Heating cab / Air-conditioned cab / ROPS / Canopy

CHARACTERISTICS:

- Adopting a well-known American brand to strengthen and upgrade the chassis, the thickness of the shell is increased by 15%, and the strength is greatly improved.
- The gearbox and rear axle housing are made of ductile iron, which has twice the compressive strength of gray iron and higher reliability.
- It adopts a high-strength and airtight special front axle, which has good waterproofness and is purchased from the same channel as a well-known American brand; the overall structure design is more scientific and the ground clearance is large, which is more suitable for paddy field operations.
- Exquisite interiors and luxurious seats make driving more comfortable. The cab adopts an E-frame structure to better ensure the safety of the driver.
- Adopting the Moll large modulus taper transmission system, the gear modulus is adjusted from 2.75 to 3.0, and the strength is increased while improving the transmission stability and transmission efficiency.

ST604 (40&50&60hp) Series Tractor



CHARACTERISTICS:

- Chinese high efficiency inline diesel engines with high fuel efficiency, low maintenance costs, standard heater and excellent cold start.
- 8F + 2R gearbox with simple operation and convenient maintenance.
- Optional single / double acting couplings for different needs and operations.
- Farmland tires, turf tires, construction tires and many other tires for various working conditions. Suitable for greenhouse plants, orchards, vegetable gardens, etc.

技术参数 / TECHNICAL PARAMETERS:

发动机功率 (千瓦) / Rated Engine Power(Kw)	29.4/36.8/44.2	轴距 (毫米) / Wheel Base(mm)	1985
驱动形式 / Driven Type	4×4 轮式 4WD	档位 / Shifts	8+2
长 (毫米) / Length (mm)	3670	最大牵引力 (四轮驱动) (千牛) / Max Traction (4WD)(KN)	≥12
宽 (毫米) / Width (mm)	1620	前进速度范围 (千米/小时) / Forward Speed Range(Km/h)	2.26-34.21
高 (毫米) / Height (mm)	2450	倒退速度范围 (千米/小时) / Reverse Speed (Km/h)	2.10-31.66
前轮轮距 (毫米) / Tread of Front Wheel(mm)	970/920/1040	动力输出轴 (转/分) / PTO(Rev./min)	540/720
后轮轮距 (毫米) / Tread of Rear Wheel(mm)	1070/1050/1170	PTO 花键数 / PTO spline number	6
轮胎规格 / Tire specifications	6.50-16/11.2-24	操作重量 / Operating weight	1738

选装：风扇驾驶室 / 暖风驾驶室 / 摆式牵引 / 防翻架 / 遮阳篷 / 8+8 模式换挡
Optional: Fan cab / Heating cab / Swing draw bar / ROPS / Canopy / 8+8 Shuttle-type

ST504 (40&50&60hp) Series Tractor



CHARACTERISTICS:

- Chinese high efficiency inline diesel engines with high fuel efficiency, low maintenance costs, standard heater and excellent cold start.
- 8F + 2R gearbox with simple operation and convenient maintenance.
- Optional single / double acting couplings for different needs and operations.
- Farmland tires, turf tires, construction tires and many other tires for various working conditions. Suitable for greenhouse plants, orchards, vegetable gardens, etc.

技术参数 / TECHNICAL PARAMETERS:

发动机功率 (千瓦) / Rated Engine Power(Kw)	29.4/36.8/44.2	轴距 (毫米) / Wheel Base(mm)	1995
驱动形式 / Driven Type	4×4 轮式 4WD	档位 / Shifts	8+2
长 (毫米) / Length (mm)	3670	最大牵引力 (四轮驱动) (千牛) / Max.Traction (4WD)(KN)	≥12
宽 (毫米) / Width(mm)	1620	前进速度范围 (千米/小时) / Forward Speed Range(Km/h)	2.26-34.21
高 (毫米) / Height (mm)	2450	倒退速度范围 (千米/小时) / Reverse Speed (Km/h)	2.10-31.86
前轮轮距 (毫米) / Tread of Front Wheel(mm)	970/920/1040	动力输出轴 (转/分) / PTO(Rcv./min)	540/720
后轮轮距 (毫米) / Tread of Rear Wheel(mm)	1070/1050/1170	PTO 花键数 / PTO spline number	6
轮胎规格 / Tire specifications	6.50-16/11.2-24	操作重量 / Operating weight	1738

选装: 风扇驾驶室 / 暖风驾驶室 / 摆式牵引 / 防翻架 / 遮阳蓬 / 8+8 模式换挡
Optional: Fan cab / Heating cab / Swing draw bar / ROPS / Canopy / 8+8 Shuttle-type

ST504 (25&30&35&40&50hp) Series Tractor



技术参数 / TECHNICAL PARAMETERS:

发动机功率 (千瓦) / Rated Engine Power(Kw)	18.4/22.1/25.7/29.4/36.8	轴距 (毫米) / Wheel Base(mm)	1200
驱动形式 / Driven Type	4×4 轮式 4WD	档位 / Shifts	8+2
长 (毫米) / Length (mm)	3350-3400	最大牵引力 (四轮驱动) (千牛) / Max Traction (4WD)(kN)	7.2/7.6/8
宽 (毫米) / Width (mm)	960-1560	前进速度范围 (千米/小时) / Forward Speed Range(Km/h)	2.06-31.30
高 (毫米) / Height (mm)	2000	倒退速度范围 (千米/小时) / Reverse Speed (Km/h)	2.71-12.52
前轮轴距 (毫米) / Traxel of Front Wheel(mm)	960/1100/1300	动力输出轴 (转/分) / PTO(Rav./min)	720/540
后轮轴距 (毫米) / Traxel of Rear Wheel(mm)	960	PTO 花键数 / PTO spline number	6
轮胎规格 / Tire specifications	6.00-16/9.50-24	操作重量 / Operating weight	1645-1745

选装: 风扇驾驶室 / 座式牵引 / 防滚架 / 遮阳篷
Optional: Fan cab / Swing draw bar / ROPS / Canopy

CHARACTERISTICS:

- Classic removable cockpit.
- The famous brand front drive axle is highly reliable.
- Adopting a new type of high pressure lifter makes the work more convenient and flexible.
- Equipped with external double oil cylinders, the working effect is better.
- Uses 8 + 2 shift, reasonable speed matching and high working efficiency.
- The power output speed can be selected from various speeds, such as 540/720 rpm, and it can be equipped with a variety of agricultural machines and tools that have a wider adaptation range.

ST254 (25&30&35&40&50hp) Series Tractor



技术参数 / TECHNICAL PARAMETERS:

发动机功率 (千瓦) / Rated Engine Power(Kw)	18.4/22.1/25.7/29.4/36.8	轴距 (毫米) / Wheel Base(mm)	1200
驱动形式 / Driven Type	4×4 轮式 4WD	档位 / Shifts	6+2
长 (毫米) / Length (mm)	3350-3400	最大牵引力 (四轮驱动) (千牛) / Max.Traction (4WD)(kN)	7.2/7.6/8
宽 (毫米) / Width (mm)	960-1560	前进速度范围 (千米/小时) / Forward Speed Range(Km/h)	2.06-31.30
高 (毫米) / Height (mm)	2000	倒退速度范围 (千米/小时) / Reverse Speed (Km/h)	2.71-12.52
前轮轮距 (毫米) / Tread of Front Wheel(mm)	960/1100/1300	动力输出轴 (转/分) / PTO(Rov./min)	720/540
后轮轮距 (毫米) / Tread of Rear Wheel(mm)	960	PTO 花键数 / PTO spline number	6
轮胎规格 / Tire specifications	6.00-16/9.50-24	操作重量 / Operating weight	1645-1745
选装: 风冷驾驶室 / 摆式牵引 / 防翻架 / 遮阳篷 Optional: Fan cab / Swing draw bar / ROPS / Canopy			

CHARACTERISTICS:

- Classic removable cockpit.
- The famous brand front drive axle is highly reliable.
- Adopting a new type of high pressure lifter makes the work more convenient and flexible.
- Equipped with external double oil cylinders, the working effect is better.
- Uses 8 + 2 shift, reasonable speed matching and high working efficiency.
- The power output speed can be selected from various speeds, such as 540/720 rpm, and it can be equipped with a variety of agricultural machines and tools that have a wider adaptation range.

ST504M (40&50&60hp) Multi-function Tractor



技术参数 / TECHNICAL PARAMETERS:

发动机功率 (千瓦) / Rated Engine Power (Kw)	29.4/36.8/44.1	轴距 (毫米) / Wheel Base (mm)	1810-1880
驱动形式 / Driven Type	4x4 轮式 4WD	档位 / Shifts	8+2
长 (毫米) / Length (mm)	3100-3300	最大牵引力 (四轮驱动) (千牛) / Max Traction (4WD) (kN)	8.75/9/11
宽 (毫米) / Width (mm)	1230-1460	前进速度范围 (千米/小时) / Forward Speed Range (km/h)	1.86-2.81
高 (毫米) / Height (mm)	2000-2100	倒退速度范围 (千米/小时) / Reverse Speed (km/h)	2.52-11.65
前轮轮距 (毫米) / Tread of Front Wheel (mm)	1030/1230/1200	动力输出轴 (转/分) / PTO (Rev./min)	720/540
后轮轮距 (毫米) / Tread of Rear Wheel (mm)	1000	PTO 花键数 / PTO spline number	6
轮胎规格 / Tire specifications	6.00-12/ 9.5-16	操作重量 / Operating weight	1695-1779
选装: 防翻架 / 遮阳篷 Optional: ROPS / Canopy			

CHARACTERISTICS:

- The famous brand front drive axle is highly reliable.
- Adopting a new type of high pressure lifter makes the work more convenient and flexible.
- Equipped with external double oil cylinders, the working effect is better.
- Uses 8 + 2 shift, reasonable speed matching and high working efficiency.
- The power output speed can be selected from various speeds, such as 540/720 rpm, and it can be equipped with a variety of agricultural machines and tools that have a wider adaptation range.

ST504 (35&40&50hp) Multi-function Tractor



技术参数 / TECHNICAL PARAMETERS:

发动机功率 (千瓦) / Rated Engine Power(Kw)	25.7/29.4/35.8	轴距 (毫米) / Wheel Base(mm)	1810-1880
驱动形式 / Driven Type	4×4 轮式 4WD	档位 / Shifts	8+2
长 (毫米) / Length (mm)	3100-3300	最大牵引力 (四轮驱动) (千牛) / Max.Trachion (4WD)(KN)	8.5/8.75/9
宽 (毫米) / Width(mm)	1230-1460	前进速度范围 (千米 / 小时) / Forward Speed Range(Km/h)	1.86-2.81
高 (毫米) / Height (mm)	2000-2100	倒退速度范围 (千米 / 小时) / Reverse Speed (Km/h)	2.52-11.65
前轮轮距 (毫米) / Tread of Front Wheel(mm)	1030/1230/1200	动力输出轴 (转 / 分) / PTO(Rov./min)	720/540
后轮轮距 (毫米) / Tread of Rear Wheel(mm)	1000	PTO 花键数 / PTO spline number	6
轮胎规格 / Tire specifications	6.00-12/ 9.5-15	操作重量 / Operating weight	1695-1779
选装: 防翻架 / 遮阳篷 Optional: ROPS / Canopy			

CHARACTERISTICS:

- The famous brand front drive axle is highly reliable.
- Adopting a new type of high pressure lifter makes the work more convenient and flexible.
- Equipped with external double oil cylinders, the working effect is better.
- Uses 8 + 2 shift, reasonable speed matching and high working efficiency.
- The power output speed can be selected from various speeds, such as 540/720 rpm, and it can be equipped with a variety of agricultural machines and tools that have a wider adaptation range.

► 为了大地的丰收
For Bumper Harvest

► 农业机械专家
Agricultural Machinery Expert



SHENGTUO TRACTOR



WhatsApp: +86-13806461474



Wechat: +86-13806461474



Phone: +86-13806461474



E-mail: sdtractor@outlook.com